

## UREA SOLUTION PRODUCTION

It is important to understand the properties of dry Urea when added to water. The reaction is endothermic. This is a negative heat reaction. When added to water the liquid becomes cold. Once the liquid becomes very cold the dissolution stops. To drive the dissolution to completion it is necessary to have vigorous agitation, more liquid to dissolve into or heat. This is usually in the form of hot water or steam.

### PRODUCT NOTES:

**UREA:** Urea (46-0-0) is a prilled, light weight product. It can be used to make Urea solutions up to 47.82% by weight, a grade of 22-0-0 Nitrogen solution. The following is a chart of various Urea solutions.

UREA – WATER SOLUTIONS						
RADE	% UREA	Ton Formula Urea * Water	Specific Gravity	LBS/GALS	SALT OUT TEMP	MINIMUM HOT WATER TEMP.
14-0-0	30.43	610	1.087	9.06	10°F	58°F
15-0-0	32.60	652	1.092	9.10	14°F	67°F
16-0-0	34.78	696	1.098	9.15	18°F	76°F
17-0-0	36.96	740	1.105	9.20	23°F	88°F
18-0-0	39.13	783	1.110	9.25	28°F	99°F
19-0-0	41.30	826	1.117	9.31	33°F	110°F
20-0-0	43.47	870	1.123	9.36	39°F	124°F
21-0-0	45.46	910	1.129	9.41	45°F	137°F
22-0-0	47.82	957	1.136	9.47	52°F	153°F
23-0-0	50.00	1000	1.147	9.57	57°F	167°F

*From experience 23-0-0 can be produced with 160 Degree F Water. Temps shown in the table are calculations based on BTU exchange*

The cooling of the liquid by the Urea must be offset with hot water. To calculate the heat required to do so is as follows. Urea has a negative heat of 110 BTU's per pound. Multiply the pounds per ton of Urea in the solution X 11 BTU's. This is the amount of negative BTU's of the Urea by the BTU's of the water. This plus the Salt Out Temperature of the solution equals the minimum hot water temperature required. Most ambient water temperatures are above the 22-0-0 solution S.O.T. of 52 degrees Fahrenheit. If the degrees of heat needed are added to the ambient water temperature it is usually sufficient to dissolve the Urea quickly.

Example:  
**22-0-0 Urea Solution**

		N	P	K
	ANALYSIS	22	0	0
MATERIAL	POUNDS	440	0	0
Water	1043			
Urea	957	440		
Total	2,000	440	0	0

**Heat to dissolve the Urea: Example calculation**

957 Pounds X -110 BTU / Pound Urea = 105,270 BTU / Ton  
105,270 BTU ÷ (1043 Pounds Water x 1 BTU/F°) = 101° the  
water will cool. 101° + cold water temp (or S.O.T.) =  
Temperature of water to mixer. 101° + 52° = 153° F. Water at  
153° F should be adequate for total dissolution of the Urea.

**50% UREA SOLUTION TEMPERATURE CALCULATION**

50% Urea solution has a S.O.T. (Salt Out Temperature) of 57 Deg. F.

Typical Calculation: 50% Solution, 1,000 Pounds Water  
1,000 Pounds Urea  
2,000 Pounds Total

Urea = -110 BTU per pound (-110 x 1,000 pounds = 110,000 negative BTU's

**The Minimum Hot Water Temperature to Achieve Total Dissolution of the Urea.**

110,000 BTU ÷ (1,000 Pounds Water x 1 BTU/F°) = 110° F the Water will Cool  
Salt Out = 57° F  
110° F + S.O.T. 57° F = 167° F Minimum Hot Water Temperature to Dissolve the  
1,000 Pounds of Urea

**Desired Finish Product Temperature 80°F**

110° F the Water will Cool + 80° F Desired = 190° F Production  
Water Temperature.

CaNO<sub>3</sub>, KNO<sub>3</sub>, KTS,  
CaTS, Amm. Sulfate,  
Urea, Etc.